

# Industrial Series

in painted steel  
Oil - Antifreeze and allied products  
150 bar

Swivel: Steel  
Seals: Polyurethane  
Hose: Black synthetic rubber



S. 560



S. 530



S. 300

	Dimension	Length (m)	Hose	Flow	Inlet	Outlet	Item
Series 300	Without hose	-	-	18 l/min	F 1/2" G	F 3/8" - F 1/2" G	I300/40
	1/2"	8	rubber	13 l/min	F 1/2" G	M 1/2" G	I300/41
	3/8"	12	rubber	11 l/min	F 1/2" G	M 1/2" G	I300/42
Series 350	Without hose	-	-	18 l/min	F 1/2" G	F 3/8" - F 1/2" G	I350/40
	1/2"	10	rubber	12 l/min	F 1/2" G	M 1/2" G	I350/41
	3/8"	17	rubber	9 l/min	F 1/2" G	M 1/2" G	I350/42
	3/8"	12	rubber	11 l/min	F 1/2" G	M 1/2" G	I350/43
Series 430	Without hose	-	-	20 l/min	F 1/2" G	F 1/2" G	I430/40
	1/2"	10	rubber	14 l/min	F 1/2" G	M 1/2" G	I430/41
	1/2"	15	rubber	12 l/min	F 1/2" G	M 1/2" G	I430/42
Series 530	Without hose	-	-	20 l/min	F 1/2" G	F 1/2" G	I530/40
	1/2"	20	rubber	10 l/min	F 1/2" G	M 1/2" G	I530/41
	1/2"	25	rubber	9 l/min	F 1/2" G	M 1/2" G	I530/42
Series 540	Without hose	-	-	40 l/min	F 1" G	F 1" G	I540/40
	1"	15	rubber	35 l/min	F 1" G	M 1" G	I540/41
	3/4"	15	rubber	30 l/min	F 1" G	M 3/4" G	I540/42
	3/4"	20	rubber	26 l/min	F 1" G	M 3/4" G	I540/43
	Without hose	-	-	20 l/min	F 1/2" G	F 1/2" G	I540/45
	1/2"	30	rubber	8 l/min	F 1/2" G	M 1/2" G	I540/46
Series 560	Without hose	-	-	40 l/min	F 1" G	F 1" G	I560/40
	3/4"	30	rubber	22 l/min	F 1" G	M 3/4" G	I560/41
	3/4"	35	rubber	20 l/min	F 1" G	M 3/4" G	I560/42
	3/4"	40	rubber	18 l/min	F 1" G	M 3/4" G	I560/43
	1"	20	rubber	32 l/min	F 1" G	M 1" G	I560/44
	1"	30	rubber	30 l/min	F 1" G	M 1" G	I560/45
	Without hose	-	-	20 l/min	F 1/2" G	F 1/2" G	I560/46
	1/2"	40	rubber	7 l/min	F 1/2" G	M 1/2" G	I560/47
	1/2"	50	rubber	6 l/min	F 1/2" G	M 1/2" G	I560/48
	1/2"	60	rubber	5 l/min	F 1/2" G	M 1/2" G	I560/49



Fixed and swivelling bracket see page 40-41