

# Industrial Series

enclosed in painted steel / technopolimer  
Air / cold water, oil and grease

Swivel: Brass  
Seals: Viton  
Hose: SBR/EPDM



S. 440.



S. 260

Painted steel  
Air / water  
20 bar

Swivel: Brass  
Seals: Viton  
Hose: Black synthetic rubber

|            | Dimension    | Length (m) | Hose   | Flow      | Inlet    | Outlet   | Item    |
|------------|--------------|------------|--------|-----------|----------|----------|---------|
| Series 440 | Without hose | -          | -      | 800 l/min | F 1/2" G | F 1/2" G | I440/10 |
|            | 1/2"         | 15         | rubber | 760 l/min | F 1/2" G | M 1/2" G | I440/11 |
|            | 3/8"         | 12         | rubber | 690 l/min | F 1/2" G | M 3/8" G | I440/12 |
|            | 3/8"         | 18         | rubber | 640 l/min | F 1/2" G | M 3/8" G | I440/13 |
|            | 1/2"         | 10         | rubber | 780 l/min | F 1/2" G | M 1/2" G | I440/14 |

Painted steel  
Oil  
150 bar

Swivel: Steel  
Seals: Polyurethane  
Hose: Black rubber

|            | Dimension    | Length (m) | Hose   | Flow     | Inlet    | Outlet   | Item    |
|------------|--------------|------------|--------|----------|----------|----------|---------|
| Series 440 | Without hose | -          | -      | 20 l/min | F 1/2" G | F 1/2" G | I440/40 |
|            | 1/2"         | 10         | rubber | 14 l/min | F 1/2" G | M 1/2" G | I440/41 |
|            | 1/2"         | 15         | rubber | 12 l/min | F 1/2" G | M 1/2" G | I440/42 |

Painted steel  
Grease  
600 bar

Swivel: Steel  
Seals: Polyurethane  
Hose: Black rubber

|            | Dimension    | Length (m) | Hose   | Flow       | Inlet    | Outlet   | Item    |
|------------|--------------|------------|--------|------------|----------|----------|---------|
| Series 440 | Without hose | -          | -      | 1200 g/min | F 3/8" G | F 1/2" G | I440/50 |
|            | 1/4"         | 12         | rubber | 650 g/min  | F 3/8" G | M 1/4" G | I440/51 |
|            | 1/4"         | 18         | rubber | 550 g/min  | F 3/8" G | M 1/4" G | I440/52 |
|            | 3/8"         | 10         | rubber | 800 g/min  | F 3/8" G | M 1/4" G | I440/55 |
|            | 3/8"         | 15         | rubber | 750 g/min  | F 3/8" G | M 1/4" G | I440/56 |

Enclosed in shock resistant technopolimer  
Air / cold water  
20 bar

Swivel: Brass  
Seals: Viton  
Hose: Polyurethane

|            | Dimension | Length (m) | Hose | Flow      | Inlet    | Outlet   | Item    |
|------------|-----------|------------|------|-----------|----------|----------|---------|
| Series 260 | 8/12mm    | 11         | PU   | 350 l/min | M 1/4" G | M 1/4" G | I261/11 |
|            | 6/10mm    | 11         | PU   | 280 l/min | M 1/4" G | M 1/4" G | I261/12 |



Fixed and swivelling bracket see page 40-41