




Nominal Diameter

7,2 = 40 mm²

RECTUS Series



26KB

actual size

**Technical Description**

European standard industrial profile. Universal brass coupling. Small massive design. Ergonomic sleeve design prevents dirt on the valve body.

Advantages

Single handed operation.
European standard.



Working Pressure

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Chart

You will find the following alternative versions in our current catalogue on page:

- ▶ Brass/Steel Single Shut-off P. 66
- ▶ Stainless Steel P. 177
- ▶ Safety Self-Venting P. 278

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Pins
Seals
(Sleeves made of thermoplastic on request)

Standard

Brass
Brass
Brass
Brass
AISI 301
AISI 420
NBR

Nickel Plated

Brass, Nickel Plated
Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
AISI 420
NBR

Plug

Plug Profile
Back Body
Valve
Spring
Seal

Brass
Brass
Brass
AISI 301
NBR

Brass, Nickel Plated
Brass, Nickel Plated
Brass
AISI 301
NBR





Couplings**RECTUS Series 26KB**

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS
<p>Male Thread</p>	G 1/8	22	43	25	9					Standard	26KB AW10 MPX	■ □
										Nickel Plated	26KB AW10 MPN	■ □
	G 1/4	22	39	25	9					Standard	26KB AW13 MPX	■ ■
										Nickel Plated	26KB AW13 MPN	■ ■
	G 3/8	22	41	25	9					Standard	26KB AW17 MPX	■ ■
										Nickel Plated	26KB AW17 MPN	■ ■
	G 1/2	24	42	25	10					Standard	26KB AW21 MPX	■ ■
										Nickel Plated	26KB AW21 MPN	■ ■

DS = Delivery Status: ■ in stock

□ on short call

■ □ medium term delivery

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS	
 <p>Male Thread</p>	M 16 x 1,5	22	43	25	11					Standard	26KB AD16 MPX	■	
										Nickel Plated	26KB AD16 MPN	■	
	M 18 x 1,5	22	43	25	11					Standard	26KB AD18 MPX	■	
										Nickel Plated	26KB AD18 MPN	■	
 <p>Female Thread</p>	G 1/4	22	41	25	9					Standard	26KB IW13 MPX	■	
										Nickel Plated	26KB IW13 MPN	■	
	G 3/8	22	41	25	9					Standard	26KB IW17 MPX	■	
										Nickel Plated	26KB IW17 MPN	■	
	G 1/2	24	44	25	10					Standard	26KB IW21 MPX	■	
										Nickel Plated	26KB IW21 MPN	■	
 <p>Hose Barb</p>	M 16 x 1,5	22	44	25	9					Standard	26KB IM16 MPX	■	
										Nickel Plated	26KB IM16 MPN	■	
	M 18 x 1,5	22	44	25	9					Standard	26KB IM18 MPX	■	
										Nickel Plated	26KB IM18 MPN	■	
 <p>Hose Barb</p>	6 mm	21	58	25	25					Standard	26KB TF06 MPX	■	
										Nickel Plated	26KB TF06 MPN	■	
	8 mm	21	58	25	25					Standard	26KB TF08 MPX	■	
										Nickel Plated	26KB TF08 MPN	■	
	9 mm	21	58	25	25					Standard	26KB TF09 MPX	■	
										Nickel Plated	26KB TF09 MPN	■	
	10 mm	21	58	25	25					Standard	26KB TF10 MPX	■	
										Nickel Plated	26KB TF10 MPN	■	
	13 mm	21	58	25	25					Standard	26KB TF13 MPX	■	
										Nickel Plated	26KB TF13 MPN	■	
	6 mm Parker	21	58	25	25					Standard	26KB TP06 MPX	■	
										Nickel Plated	26KB TP06 MPN	■	





DS = Delivery Status: ■ in stock

■ on short call

■ medium term delivery

Couplings

RECTUS Series 26KB

	Connection A	Hex SW	L mm	D mm	L1 mm	L2 mm	Hex1 SW1	B mm	G mm	Version	Part Number	DS
 <p>Hose Barb</p>	10 mm Parker	21	58	25	24					Standard	26KB TP10 MPX	■
										Nickel Plated	26KB TP10 MPN	■
	13 mm Parker	21	58	25	28					Standard	26KB TP13 MPX	■
										Nickel Plated	26KB TP13 MPN	■
 <p>Plastic Hose Connection</p>	6 x 8 mm	21	45	25	7	6			M 12 x 1	Standard	26KB KO08 MPX	■
										Nickel Plated	26KB KO08 MPN	■
	8 x 10 mm	21	49	25	9	8			M 16 x 1	Standard	26KB KO10 MPX	■
										Nickel Plated	26KB KO10 MPN	■
 <p>Panel Mount, Hose Barb</p>	6 mm	21	60	25	17	10	17	4	M 12 x 1	Standard	26KB TS06 MPX	■
										Nickel Plated	26KB TS06 MPN	■
	8 mm	21	63	25	17	14	17	4	M 12 x 1	Standard	26KB TS08 MPX	■
										Nickel Plated	26KB TS08 MPN	■
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	21	132	25	7	6			M 12 x 1	Standard	26KB KK08 MPX	■
										Nickel Plated	26KB KK08 MPN	■
	8 x 10 mm	21	143	25	9	8			M 16 x 1	Standard	26KB KK10 MPX	■
										Nickel Plated	26KB KK10 MPN	■
	9 x 12 mm	21	150	25	9	8			M 16 x 1	Standard	26KB KK12 MPX	■
										Nickel Plated	26KB KK12 MPN	■

Valved Plugs for all 26 KB Series (same as 25KB Series!) see page 137.

DS = Delivery Status: ■ in stock

■ on short call

■ medium term delivery